

Package: crosstable (via r-universe)

October 14, 2026

Title Crosstables for Descriptive Analyses

Version 0.9.0.9009

Description Create descriptive tables for continuous and categorical variables. Apply summary statistics and counting function, with or without a grouping variable, and create beautiful reports using 'rmarkdown' or 'officer'. You can also compute effect sizes and statistical tests if needed.

License GPL-3

URL <https://danchaltiel.github.io/crosstable/>,
<https://github.com/DanChaltiel/crosstable/>

BugReports <https://github.com/DanChaltiel/crosstable/issues/>

Depends R (>= 3.6.0)

Imports checkmate (>= 1.9.0), cli (>= 3.0.0), dplyr (>= 1.1.0),
flextable (>= 0.5.1), forcats (>= 1.0.0), glue (>= 1.3.0),
lifecycle (>= 0.2.0), officer (>= 0.4.0), purrr (>= 0.2.3),
rlang (>= 1.0.0), stats, stringr (>= 1.4.0), tibble (>= 1.1),
tidyr (>= 1.0.0), utils,

Suggests callr, covr, crayon, xml2, digest, gt, expss, ggplot2,
gmodels, Hmisc, hms, jsonlite, knitr, lubridate, openxlsx,
rmarkdown, sloop, stringi, survival, systemfonts, tidyselect,
testthat (>= 3.0.0), withr, waldo

VignetteBuilder knitr

Encoding UTF-8

LazyData true

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.2

Config/testthat/edition 3

Config/testthat/parallel true

Config/testthat/start-first by_factor , effects_snap, officer

Config/pak/sysreqs

libcairo2-dev cmake libfontconfig1-dev libfreetype6-dev libfribidi-dev make libharfbuzz-dev libicu-dev libjpeg-dev libpng-dev libtiff-dev libuv1-dev libwebp-dev libxml2-dev libssl-dev

Repository <https://danchaltiel.r-universe.dev>

Date/Publication 2026-09-14 15:10:55 UTC

RemoteUrl <https://github.com/DanChaltiel/crosstable>

RemoteRef HEAD

RemoteSha fd7a8ec1e55835acf6f5583bd10f5a9daf2309b3

Contents

apply_labels	3
as_flextable.crosstable	4
as_gt.crosstable	6
as_workbook	8
body_add_crosstable	9
body_add_crosstable_footnote	10
body_add_flextable2	11
body_add_gg2	12
body_add_img2	13
body_add_legend	14
body_add_list	17
body_add_normal	19
body_add_table_list	21
body_add_table_section	22
body_add_title	23
body_replace_text_at_bkms	25
clean_names_with_labels	26
confint_numeric	27
cross_summary	27
crosstable	28
crosstable_effect_args	31
crosstable_options	32
crosstable_peek_options	37
crosstable_reset_options	37
crosstable_test_args	38
ct_bind_cols	39
ct_compact	40
display_effect	41
display_test	42
docx_bookmarks2	42
effect_summary	43
effect_survival	44
effect_tabular	45
format_fixed	46
generate_autofit_macro	47

get_label	48
get_percent_pattern	50
import_labels	50
iris2	52
is.crosstable	53
mtcars2	53
N	54
na	55
narm	55
peek	56
pivot_crosstable	56
plim	57
remove_labels	57
rename_with_labels	58
set_label	59
summaryFunctions	60
test_correlation_auto	61
test_summarize_auto	62
test_summarize_linear_contrasts	63
test_survival_logrank	63
test_tabular_auto	64
transpose_crosstable	65
write_and_open	65
Index	67

apply_labels	<i>Batch set variable labels</i>
--------------	----------------------------------

Description

This function is a copycat of from expss package v0.10.7 (slightly modified) to avoid having to depend on expss. See [expss::apply_labels\(\)](#) for more documentation. Note that this version is not compatible with data.table.

Usage

```
apply_labels(.data, ..., fn, warn_missing = FALSE)
```

Arguments

.data	data.frame/list
...	named arguments, as colname="label"
fn	alternatively, a function to be applied to all existing labels.
warn_missing	if TRUE, throw a warning if some names are missing

Value

An object of the same type as data, with labels

Author(s)

Dan Chaltiel

Examples

```
iris %>%
  apply_labels(Sepal.Length="Length of Sepal",
               Sepal.Width="Width of Sepal") %>%
  crosstable()
iris2 %>%
  apply_labels(fn=tolower) %>%
  crosstable()
```

```
as_flextable.crosstable
```

Turns a crosstable object into a formatted flextable

Description

Turns a crosstable object into a formatted flextable

Usage

```
## S3 method for class 'crosstable'
as_flextable(
  x,
  keep_id = FALSE,
  ...,
  by_header = NULL,
  autofit = TRUE,
  compact = FALSE,
  collapse = NULL,
  show_test_name = TRUE,
  allow_breaks = FALSE,
  fontsizes = list(body = 11, subheaders = 11, header = 11),
  padding_v = NULL,
  remove_header_keys = TRUE,
  header_show_n = FALSE,
  header_show_n_pattern = "{.col} (N={.n})",
  generic_labels = list(id = ".id", variable = "variable", value = "value", total =
    "Total", label = "label", test = "test", effect = "effect")
)

as_flextable(x, ...)
```

Arguments

x	the result of <code>crosstable()</code> .
keep_id	whether to keep the <code>.id</code> column.
...	unused.
by_header	a string to override the header if x has only one by stratum.
autofit	whether to automatically adjust the table. Can also be a function.
compact	whether to compact the table. If TRUE, see <code>ct_compact.crosstable()</code> to see how to use <code>keep_id</code> .
collapse	levels to collapse when in compact format. Ignored if <code>compact!=TRUE</code> . See examples.
show_test_name	in the test column, show the test name.
allow_breaks	whether to allow the table to break on .
fontsizes	font sizes as a list of keys. Default to <code>list(body=11, subheaders=11, header=11)</code> . If set through arguments instead of options, all 3 names should be specified.
padding_v	vertical padding (body).
remove_header_keys	if TRUE and x has several by strata, header will only display values.
header_show_n	numeric vector telling on which depth the group size should be indicated in the header. You can control the pattern using option <code>crosstable_options</code> . See <code>crosstable_options()</code> for details about it. See example for use case.
header_show_n_pattern	glue pattern used when <code>header_show_n==TRUE</code> . <code>.col</code> is the name of the column and <code>.n</code> the size of the group. Default to <code>{.col}</code> (<code>N={.n}</code>); you can also use <code>{.col_key}</code> and <code>{.col_val}</code> when <code>by</code> has multiple stratum. To control the "Total" column, enter this as a list with names "cell" and "total".
generic_labels	names of the crosstable default columns. Useful for translation for instance.

Value

a flextable.

Methods (by class)

- `as_flextable(crosstable)`: Turns a crosstable object into a formatted flextable.

Author(s)

Dan Chaitiel

See Also

`crosstable()`, `flextable::flextable()`, `as_gt.crosstable()`

Examples

```

crosstable_options(crosstable_fontsize_header=14,
                   crosstable_fontsize_subheaders=10,
                   crosstable_fontsize_body=8)
crosstable(iris) %>% as_flextable()
crosstable(mtcars2, ~model, by=c(am, vs)) %>% as_flextable(header_show_n=1)
crosstable(mtcars2, cols=c(mpg, cyl), by=am, effect=TRUE) %>%
  as_flextable(keep_id=TRUE, autofit=FALSE)
crosstable(mtcars2, cols=c(mpg, cyl), by=am, effect=TRUE, total=TRUE) %>%
  as_flextable(compact=TRUE, header_show_n=TRUE,
              header_show_n_pattern=list(cell="{.col} (N={.n})", total="Total\n(N={.n})"))

#collapse levels
mtcars2 %>%
  dplyr::mutate(am_man = forcats::fct_recode(am, "Yes"="manual", "No"="auto")) %>%
  apply_labels(am_man="Manual transmission") %>%
  crosstable(c(mpg, am_man, hp), by=vs, test=TRUE, effect=TRUE) %>%
  as_flextable(compact=TRUE, collapse="Yes")

#Renaming (because why not?)
crosstable(mtcars2, am, by=vs, total="both", test=TRUE, effect=TRUE) %>%
  dplyr::rename(ID=.id, math=variable, Tot=Total, lab=label, pval=test, fx=effect) %>%
  as_flextable(by_header = "Engine shape",
              generic_labels=list(id = "ID", variable = "math", total="Tot",
                                label = "lab", test = "pval", effect="fx"))

```

as_gt.crosstable

Converts a crosstable object into a formatted gt table.

Description

Converts a crosstable object into a formatted gt table.

Method to convert an object to a gt table

Default method to convert an object to a gt table

Usage

```

## S3 method for class 'crosstable'
as_gt(
  x,
  show_test_name = TRUE,
  by_header = NULL,
  keep_id = FALSE,
  generic_labels = list(id = ".id", variable = "variable", value = "value", total =
    "Total", label = "label", test = "test", effect = "effect"),
  ...
)

```

```
as_gt(x, ...)  
  
## Default S3 method:  
as_gt(x, ...)
```

Arguments

x	object to be converted
show_test_name	in the test column, show the test name
by_header	a string to override the by header
keep_id	whether to keep the .id column
generic_labels	names of the crosstable default columns
...	arguments for custom methods

Value

a formatted gt table

Methods (by class)

- `as_gt(crosstable)`: For crosstables
- `as_gt(default)`: default function

Author(s)

Dan Chaitiel

See Also

```
as\_flextable.crosstable\(\)  
gt::gt\(\)
```

Examples

```
xx = mtcars2 %>% dplyr::select(2:10)  
crosstable(xx) %>% as_gt  
crosstable(xx, by=am) %>% as_gt  
crosstable(xx, by=cyl, test=TRUE, total=TRUE) %>%  
  as_gt(keep_id=TRUE, show_test_name=FALSE, by_header="Cylinders")
```

as_workbook	<i>Converts a crosstable object into a formatted, savable openxlsx workbook.</i>
-------------	--

Description

Converts a crosstable object into a formatted, savable openxlsx workbook.

Usage

```
as_workbook(
  x,
  show_test_name = TRUE,
  by_header = NULL,
  keep_id = FALSE,
  generic_labels = list(id = ".id", variable = "variable", value = "value", total =
    "Total", label = "label", test = "test", effect = "effect"),
  ...
)
```

Arguments

x	the result of <code>crosstable()</code> or a list of crosstables
show_test_name	in the test column, show the test name
by_header	a string to override the by header
keep_id	whether to keep the .id column
generic_labels	names of the crosstable default columns
...	unused

Value

an openxlsx workbook containing the crosstable(s)

Author(s)

Dan Chaitiel

Examples

```
library(openxlsx)
target = tempfile(fileext=".xlsx")

x=crosstable(mtcars2, c(mpg, vs, gear), total=TRUE, test=TRUE)
as_workbook(x, keep_id=TRUE) %>%
  saveWorkbook(file=target)
if(interactive()) browseURL(target)
```

```
target = tempfile(fileext=".xlsx")
x2=list(iris=crosstable(iris2), crosstable(mtcars2))
as_workbook(x2, keep_id=TRUE) %>%
  saveWorkbook(file=target)
if(interactive()) browseURL(target)
```

body_add_crosstable *Add a crosstable to an officer document*

Description

`body_add_crosstable()` adds such a flextable an officer document.

Usage

```
body_add_crosstable(
  doc,
  x,
  body_fontsize = NULL,
  header_fontsize = ceiling(body_fontsize * 1.2),
  padding_v = NULL,
  allow_break = TRUE,
  max_cols = 25,
  ...
)
```

Arguments

<code>doc</code>	a rdocx object, created by <code>officer::read_docx()</code>
<code>x</code>	a crosstable object
<code>body_fontsize</code>	fontsize of the body
<code>header_fontsize</code>	fontsize of the header. Defaults to $1.2 \times \text{body_fontsize}$.
<code>padding_v</code>	vertical padding of all table rows
<code>allow_break</code>	allow crosstable rows to break across pages
<code>max_cols</code>	max number of columns for x
<code>...</code>	further arguments passed to <code>as_flextable.crosstable()</code>

Value

The docx object doc

Author(s)

Dan Chaltiel

Examples

```
#Officer
library(officer)
mytable = crosstable(mtcars2)
doc = read_docx() %>%
  body_add_crosstable(mytable) %>%
  body_add_break %>%
  body_add_crosstable(mytable, compact=TRUE)

dfile = tempfile(fileext=".docx")
print(doc, target = dfile)
if(interactive()) browseURL(dfile)
```

body_add_crosstable_footnote

Adds a standard footnote explaining the abbreviations used in a crosstable

Description

Use it below [body_add_crosstable\(\)](#). Footnote: Med: median, IQR: interquartile range, Std: standard deviation. Percentages are expressed in column.

Usage

```
body_add_crosstable_footnote(doc)
```

Arguments

doc a rdocx object

Value

The docx object doc

Author(s)

Dan Chaltiel

body_add_flextable2 *Alternative to `flextable::body_add_flextable()`*

Description

Extends `body_add_flextable()` by adding:

- a legend (if `x` has a "legend" attribute), via `body_add_table_legend()`
- an optional empty line after the table

Usage

```
body_add_flextable2(doc, x, bookmark = NULL, append_line = TRUE, ...)
```

Arguments

<code>doc</code>	An rdocx object from officer .
<code>x</code>	A flextable object. If it has a "legend" attribute, it is added.
<code>bookmark</code>	Optional. Word bookmark name for the legend.
<code>append_line</code>	Whether to add an empty line after the table.
<code>...</code>	Passed to <code>flextable::body_add_flextable()</code> .

Value

The docx object `doc`

Examples

```
library(officer)
library(ggplot2)
ft = flextable::flextable(head(iris)) %>%
  structure(legend="The iris dataset")

doc = read_docx() %>%
  body_add_normal("Text before") %>%
  body_add_flextable2(ft) %>%
  body_add_normal("Text after")
write_and_open(doc)
```

body_add_gg2

*Alternative to `officer::body_add_gg()` which uses ggplot syntax***Description**

Alternative to `officer::body_add_gg()` which uses ggplot syntax

Usage

```
body_add_gg2(
  doc,
  value,
  width = getOption("crosstable_gg_width", 6),
  height = getOption("crosstable_gg_height", 5),
  units = getOption("crosstable_units", "in"),
  style = getOption("crosstable_style_image", doc$default_styles$paragraph),
  add_legend = TRUE,
  bookmark = NULL,
  res = 300,
  ...
)
```

Arguments

<code>doc</code>	An rdocx object from officer .
<code>value</code>	ggplot object
<code>width, height</code>	width and height. Can be abbreviated to w and h.
<code>units</code>	units for width and height
<code>style</code>	paragraph style
<code>add_legend</code>	add a legend if the ggplot has a legend attribute (see example)
<code>bookmark</code>	the bookmark of the legend, if applicable
<code>res</code>	resolution of the png image in ppi (passed to the argument <code>dpi</code> of <code>ggplot2::ggsave()</code>)
<code>...</code>	other arguments to be passed to <code>ggplot2::ggsave()</code>

Value

The docx object doc

Author(s)

Dan Chaltiel

Examples

```
library(officer)
library(ggplot2)
p = ggplot(data=iris, aes(Sepal.Length, Petal.Length)) + geom_point()
attr(p, "legend") = "Sepal length by Petal length"
crosstable_options(
  units="cm",
  style_image="centered"
)
doc = read_docx() %>%
  body_add_normal("Text before") %>%
  body_add_gg2(p, w=14, h=10, scale=1.5) %>% #or units="cm" instead of using options
  body_add_normal("Text after")
write_and_open(doc)
```

body_add_img2	Alternative to <code>officer::body_add_img()</code> which adds a units choice
---------------	---

Description

Alternative to `officer::body_add_img()` which adds a units choice

Usage

```
body_add_img2(
  doc,
  src,
  width,
  height,
  units = getOption("crosstable_units", "in"),
  style = getOption("crosstable_style_image", doc$default_styles$paragraph),
  ...
)
```

Arguments

doc	an rdocx object
src	image filename, the basename of the file must not contain any blank.
width, height	width and height. Can be abbreviated to w and h.
units	units for width and height
style	paragraph style
...	other arguments to be passed to <code>officer::body_add_img()</code>

Value

The docx object doc

Author(s)

Dan Chaltiel

See Also[body_add_gg2\(\)](#)**Examples**

```
img.file = file.path( R.home("doc"), "html", "logo.jpg" )
if(file.exists(img.file)){
  library(officer)
  options(crosstable_units="cm")
  doc = read_docx() %>%
    body_add_normal("This is the R logo.") %>%
    body_add_img2(img.file, h=7.6, w=10, style="centered") #or units="cm" without options
  #write_and_open(doc)
}
```

body_add_legend

*Add a legend to a table or a figure***Description**

Add a legend to a table or a figure in an officer document. Legends can be referred to using the @ref syntax in [body_add_normal\(\)](#) (see examples for some use cases). Table legends should be inserted before the table while figure legends should be inserted after the figure.

Usage

```
body_add_table_legend(
  doc,
  legend,
  ...,
  bookmark = NULL,
  legend_style = getOption("crosstable_style_legend", doc$default_styles$paragraph),
  style = deprecated(),
  legend_prefix = NULL,
  name_format = NULL,
  legend_name = "Table",
  seqfield = "SEQ Table \\* Arabic",
  par_before = FALSE,
  envir = parent.frame(),
  legacy = FALSE
)

body_add_figure_legend(
  doc,
```

```

    legend,
    ...,
    bookmark = NULL,
    legend_style = getOption("crosstable_style_legend", doc$default_styles$paragraph),
    style = deprecated(),
    legend_prefix = NULL,
    name_format = NULL,
    legend_name = "Figure",
    seqfield = "SEQ Figure \\* Arabic",
    par_after = FALSE,
    envir = parent.frame(),
    legacy = FALSE
)

```

Arguments

doc	a docx object
legend	the table legend. Supports glue syntax and markdown syntax (see Section below).
...	unused
bookmark	the id of the bookmark. This is the id that should then be called in body_add_normal() using the "\\@ref(id)" syntax. Forbidden characters will be removed.
legend_style	style of of the whole legend. May depend on the docx template. However, if name_format is provided with a specific font.size, this size will apply to the whole legend for consistency.
style	deprecated in favor of name_format.
legend_prefix	a prefix that comes before the legend, after the numbering
name_format	format of the legend's LHS (legend_name + numbering) using officer::fp_text_lite() or officer::fp_text() . Default to fp_text_lite(bold=TRUE) in addition to the format defined in legend_style. Note that the reference to the bookmark will have the same specific format in the text.
legend_name	name before the numbering. Default to either "Table" or "Figure".
seqfield	Keep default. Otherwise, you may figure it out doing this: in a docx file, insert a table legend, right click on the inserted number and select "Toggle Field Codes". This argument should be the value of the field, with extra escaping.
par_before, par_after	should an empty paragraph be inserted before/after the legend?
envir	Environment to evaluate each expression in glue().
legacy	use the old version of this function, if you cannot update {officer} to v0.4+

Value

The docx object doc

Warning

Be aware that you unfortunately cannot reference a bookmark more than once using this method.

Writing:

```
body_add_normal("Table \@ref(iris_col1) is about flowers. I really like Table \@ref(iris_col1).")
```

will prevent the numbering from applying.

What to do if there is still no numbering?

During the opening of the document, MS Word might ask you to "update the fields", to which you should answer "Yes".

If it is not asked or if you answer "No", the legends added with `body_add_table_legend()` or `body_add_figure_legend()` might have no actual numbers displayed.

In this case, you have to manually update the references in MS Word: select all (Ctrl+A), then update (F9), sometimes twice. More info on <https://ardata-fr.github.io/officeverse/faq.html#update-fields>.

Markdown support

In all crosstable helpers for officer, you can use the following Markdown syntax to format your text:

- *bold*: `"**text in bold**"`
- *italics*: `"*text in italics*"`
- *subscript*: `"Text in ~subscript~"`
- *superscript*: `"Text in ^superscript^"`
- *newline*: Before `<br>` After
- *color*: `"<color:red>red text</color>"`
- *shade*: `"<shade:yellow>yellow text</shade>"` (background color)
- *font family*: `"<ff:symbol>symbol</ff>"` (

Note that the font name depends on your system language. For instant, in French, it would be Symbol with an uppercase first letter.

See the last example of `body_add_normal()` for a practical case.

Author(s)

Dan Chaltiel

Examples

```
library(officer)
library(ggplot2)
p = ggplot(iris, aes(x=Sepal.Length, y=Sepal.Width, color=Species)) + geom_point()
fp_italic = fp_text_lite(italic=TRUE, font.size=10)
x = read_docx() %>%
  body_add_normal("There is Table \@ref(iris_col1) and Table \@ref(iris_col2). ",
    "The `iris` dataset is about flowers.") %>%
  body_add_normal() %>%
```

```

body_add_table_legend("Iris dataset, column 1 (mean={round(mean(iris[[1]]), 2)}",
                      bookmark="iris_col1") %>%
body_add_crosstable(crosstable(iris[1])) %>%
body_add_normal() %>%
body_add_table_legend("Iris dataset, column 2 (mean={round(mean(iris[[2]]), 2)}",
                      bookmark="iris_col2",
                      name_format=fp_italic, legend_style="Balloon Text") %>%
body_add_crosstable(crosstable(iris[2])) %>%
body_add_normal() %>%
body_add_normal("There is also the figure \@ref(iris_fig)") %>%
body_add_gg(p) %>%
body_add_figure_legend("Iris plot", bookmark="iris_fig")
write_and_open(x)
#If asked to update fields, press "Yes". Otherwise press Ctrl+A then F9 twice for the references
#to appear.

```

body_add_list

*Add a list to an officer document***Description**

Add a list to an officer document

Usage

```
body_add_list(doc, value, ordered = FALSE, style = NULL, ...)
```

```
body_add_list_item(doc, value, ordered = FALSE, style = NULL, ...)
```

Arguments

doc	a docx object
value	a character vector (body_add_list()) or scalar (body_add_list_item). See Section below for markdown support.
ordered	if TRUE, adds an ordered list, if FALSE (default), adds a bullet list
style	specify the style manually, overriding ordered. A better way is to set options crosstable_style_list_ordered and crosstable_style_list_unordered globally.
...	passed on to <code>officer::body_add_par()</code>

Details

Ordered lists and bullet lists are not supported by the default officer template (see <https://github.com/davidgohel/officer/issues>). You have to manually set custom styles matching those list in a custom Word template file. Then, you can use either the style argument or crosstable options. See examples for more details.

Value

The docx object doc

Markdown support

In all crosstable helpers for officer, you can use the following Markdown syntax to format your text:

- *bold*: `"**text in bold**"`
- *italics*: `"*text in italics*"`
- *subscript*: `"Text in ~subscript~"`
- *superscript*: `"Text in ^superscript^"`
- *newline*: Before `<br>` After
- *color*: `"<color:red>red text</color>"`
- *shade*: `"<shade:yellow>yellow text</shade>"` (background color)
- *font family*: `"<ff:symbol>symbol</ff>"` (

Note that the font name depends on your system language. For instant, in French, it would be Symbol with an uppercase first letter.

See the last example of `body_add_normal()` for a practical case.

Author(s)

Dan Chaltiel

Examples

```
## Not run:
#For this example to work, `my_template.docx` should include styles named
#`ordered_list` and `unordered_list`

library(officer)
library(crosstable)
options(crosstable_style_list_ordered="ordered_list")
options(crosstable_style_list_unordered="unordered_list")

read_docx("my_template.docx") %>%
  body_add_list(c("Numbered item 1", "Numbered item 2"), ordered = TRUE) %>%
  body_add_list_item("Numbered item 3", ordered = TRUE) %>%
  body_add_list(c("Bullet item 1", "Bullet item 2"), ordered = FALSE) %>%
  body_add_list_item("Bullet item 3", ordered = FALSE) %>%
  write_and_open()

## End(Not run)
```

body_add_normal	<i>Add a new paragraph with default style</i>
-----------------	---

Description

Add a new paragraph in an officer document with default style.

Variables can be inserted in the text as multiple strings (`paste()` style) or enclosed by braces (`glue()` style).

Basic markdown syntax is available: **bold**, *italic*, and underlined.

References to any bookmark can be inserted using the syntax `@ref(bookmark)` and newlines can be inserted using the token `<br>`.

Usage

```
body_add_normal(
  doc,
  ...,
  .sep = "",
  style = NULL,
  squish = TRUE,
  font_size = NA,
  envir = parent.frame(),
  parse = c("ref", "format", "code")
)
```

Arguments

<code>doc</code>	the doc object (created with the <code>read_docx</code> function of officer package)
<code>...</code>	one or several character strings, pasted using <code>.sep</code> . As with <code>glue::glue()</code> , expressions enclosed by braces will be evaluated as R code. If more than one variable is passed, all should be of length 1.
<code>.sep</code>	Separator used to separate elements.
<code>style</code>	Style for normal text. Best set with crosstable_options() .
<code>squish</code>	Whether to squish the result (remove trailing and repeated spaces). Default to TRUE. Allows to add multiline paragraph without breaking the string.
<code>font_size</code>	Font size.
<code>envir</code>	Environment to evaluate each expression in <code>glue()</code> .
<code>parse</code>	which format to parse. Default to all formats (<code>c("ref", "format", "code")</code>).

Value

a new doc object

The docx object doc

Markdown support

In all crosstable helpers for officer, you can use the following Markdown syntax to format your text:

- *bold*: `"**text in bold**"`
- *italics*: `"*text in italics*"`
- *subscript*: `"Text in ~subscript~"`
- *superscript*: `"Text in ^superscript^"`
- *newline*: Before `<br>` After
- *color*: `"<color:red>red text</color>"`
- *shade*: `"<shade:yellow>yellow text</shade>"` (background color)
- *font family*: `"<ff:symbol>symbol</ff>"` (

Note that the font name depends on your system language. For instant, in French, it would be Symbol with an uppercase first letter.

See the last example of `body_add_normal()` for a practical case.

Author(s)

Dan Chaltiel

Examples

```
library(officer)
library(crosstable)

info_rows = c("Also, table iris has {nrow(iris)} rows.",
              "And table mtcars has {nrow(mtcars)} rows.")
doc = read_docx() %>%
  body_add_normal("Table iris has", ncol(iris), "columns.", .sep=" ") %>% #paste style
  body_add_normal("However, table mtcars has {ncol(mtcars)} columns") %>% #glue style
  body_add_normal(info_rows) %>% #vector style
  body_add_normal("")
doc = doc %>%
  body_add_normal("You can write text in italic1, underlined1, bold1, and `code`,
    and you can also add * **references* *, for instance a ref to Table
    @ref(my_table). Multiple spaces are ignored (squished) so that you
    can enter multiline text.") %>%
  body_add_normal() %>%
  body_add_normal("Here I should use `body_add_crosstable()` to add a table before the
    legend.") %>%
  body_add_table_legend("My pretty table", bookmark="my_table")
write_and_open(doc)

#Markdown support
read_docx() %>%
  body_add_normal("This is bold and italic (see Table @ref(my_bkm)). <br> This is
    bold `console \\*CODE\\*` and and_italic **) %>%
  body_add_normal("This is <color:red>red bold text</color>, this is ~subscript italic~,
```

```

        and this is ^superscript with <shade:yellow>yellow</shade>^") %>%
body_add_normal("This is <ff:Alibi>a fancy font</ff> and this `is code`!!") %>%
        #you might need to change "Alibi" to "alibi" here
body_add_normal() %>%
body_add_table_legend("Some table legend", bookmark="my_bkm") %>%
write_and_open()

```

body_add_table_list *Add a list of tables*

Description

Add a list of tables in an officer document. crosstables will be added using `body_add_crosstable()` and flextables will be added using `flextable::body_add_flextable()`. Plain dataframes will be converted to flextables.

Usage

```

body_add_table_list(
  doc,
  l,
  fun_before = "title2",
  fun_after = NULL,
  fun = fun_before,
  ...
)

body_add_flextable_list(...)

body_add_crosstable_list(...)

```

Arguments

doc	a rdocx object, created by <code>officer::read_docx()</code>
l	a named list of tables (of class <code>crosstable</code> , <code>flextable</code> , or <code>data.frame</code>).
fun_before	a function to be used before each table
fun_after	a function to be used after each table.
fun	Deprecated
...	arguments passed on to <code>body_add_crosstable()</code> or <code>flextable::body_add_flextable()</code>

Value

The docx object doc

fun_before **and** fun_after

These should be function of the form `function(doc, .name)` where `.name` is the name of the current table of the list. You can also pass "title2" to add the name as a title of level 2 between each table (works for levels 3 and 4 as well), "newline" to simply add a new line, or even NULL to not separate them (beware that the tables might merge then). `fun_before` is designed to add a title while `fun_after` is designed to add a table legend (cf. examples).

Examples

```
library(officer)
ctl = list(iris2=crosstable(iris2, 1),
           "Just a flextable"=flextable::flextable(mtcars2[1:5,1:5]),
           "Just a dataframe"=iris2[1:5,1:5])

fun1 = function(doc, .name){
  doc %>%
    body_add_title(" This is table '{.name}' as a flex/crosstable", level=2) %>%
    body_add_normal("Here is the table:")
}
fun2 = function(doc, .name){
  doc %>% body_add_table_legend("{.name}", bookmark=.name)
}
read_docx() %>%
  body_add_title("Separated by subtitle", 1) %>%
  body_add_table_list(ctl, fun_before="title2") %>%
  body_add_break() %>%
  body_add_title("Separated using a custom function", 1) %>%
  body_add_normal("You can therefore use bookmarks, for instance here are
                  tables \@ref(iris2), \@ref(just_a_flextable)
                  and \@ref(just_a_dataframe).") %>%
  body_add_table_list(ctl, fun_before=fun1, fun_after=fun2, body_fontsize=8) %>%
  write_and_open()
```

body_add_table_section

Add a section with a table and its legend

Description

Add a section with a table and its legend

Usage

```
body_add_table_section(
  doc,
  x,
  legend,
  ...,
```

```
bookmark = NULL,
title = getOption("crosstable_section_title", TRUE),
title_lvl = getOption("crosstable_section_title_level", 3),
sentence = getOption("crosstable_section_sentence", FALSE)
)
```

Arguments

doc	a rdocx object
x	a table: crosstable, flextable, or plain old dataframe
legend	the legend to use
...	passed on to <code>flextable::body_add_flextable()</code> or <code>body_add_crosstable()</code>
bookmark	the bookmark to use. Defaults to the cleaned variable name of x
title	the title to add for the section. Can also be FALSE (no title) or TRUE (the title defaults to legend)
title_lvl	the title level if applicable
sentence	a sentence to add between the title (if applicable) and the table. If TRUE, defaults to "Information about {tolower(title)} is described in Table @ref({bookmark})".

Value

The docx object doc

Examples

```
library(officer)
read_docx() %>%
  body_add_title("Description", 1) %>%
  body_add_title("Population A", 2) %>%
  body_add_table_section(head(iris), "The iris dataset", sentence=TRUE) %>%
  body_add_table_section(crosstable(iris), "A crosstable of the iris dataset",
                        title=FALSE, sentence=TRUE, body_fontsize=8) %>%
  write_and_open()
```

body_add_title	<i>Add a title to an officer document</i>
----------------	---

Description

Add a title to an officer document

Usage

```
body_add_title(
  doc,
  value,
  level = 1,
  squish = TRUE,
  envir = parent.frame(),
  style = getOption("crosstable_style_heading", "heading")
)
```

Arguments

<code>doc</code>	the doc object (created with the <code>read_docx</code> function of <code>officer</code> package)
<code>value</code>	a character string. See Section below for markdown support.
<code>level</code>	the level of the title. See <code>styles_info(doc)</code> to know the possibilities.
<code>squish</code>	Whether to squish the result (remove trailing and repeated spaces). Default to <code>TRUE</code> .
<code>envir</code>	Environment to evaluate each expression in <code>glue()</code> .
<code>style</code>	the name of the title style. See <code>styles_info(doc)</code> to know the possibilities.

Value

The docx object `doc`

Markdown support

In all `crosstable` helpers for `officer`, you can use the following Markdown syntax to format your text:

- *bold*: `"**text in bold**"`
- *italics*: `"*text in italics*"`
- *subscript*: `"Text in ~subscript~"`
- *superscript*: `"Text in ^superscript^"`
- *newline*: Before `<br>` After
- *color*: `"<color:red>red text</color>"`
- *shade*: `"<shade:yellow>yellow text</shade>"` (background color)
- *font family*: `"<ff:symbol>symbol</ff>"` (

Note that the font name depends on your system language. For instant, in French, it would be `Symbol` with an uppercase first letter.

See the last example of `body_add_normal()` for a practical case.

Author(s)

Dan Chaltiel

Examples

```
library(officer)
library(crosstable)
library(dplyr)
doc = read_docx() %>%
  body_add_title("La table iris (nrow={nrow(iris)})", 1) %>%
  body_add_title("Description", 2) %>%
  body_add_normal("La table iris a ", ncol(iris), " colonnes.")
#write_and_open(doc)
```

body_replace_text_at_bkms

Replace text on several bookmarks at once

Description

Replace text on several bookmarks at once

Usage

```
body_replace_text_at_bkms(doc, ..., envir = parent.frame())
```

Arguments

doc	a rdocx object
...	named
envir	Environment to evaluate each expression in glue().

Value

The docx object doc

Author(s)

Dan Chaltiel

`clean_names_with_labels`*Cleans names of a dataframe while retaining old names as labels*

Description

Cleans names of a dataframe while retaining old names as labels

Usage

```
clean_names_with_labels(  
  df,  
  except = NULL,  
  .fun = getOption("crosstable_clean_names_fun")  
)
```

Arguments

<code>df</code>	a data.frame
<code>except</code>	<code><tidy-select></code> columns that should not be renamed.
<code>.fun</code>	the function used to clean the names. Default function is <code>limited</code> ; if the cleaning is not good enough you could use <code>janitor::make_clean_names()</code>

Value

A dataframe with clean names and label attributes

Author(s)

Dan Chaltiel

Examples

```
#options(crosstable_clean_names_fun=janitor::make_clean_names)  
x = data.frame("name with space"=1, TwoWords=1, "total $ (2009)"=1, accents=1,  
              check.names=FALSE)  
cleaned = clean_names_with_labels(x, except=TwoWords)  
cleaned %>% names()  
cleaned %>% get_label()
```

confint_numeric	<i>Confidence interval of a numeric vector</i>
-----------------	--

Description

Not an S3 method, which might have conflicted with [stats::confint](#).

Usage

```
confint_numeric(object, level = 0.95, B = 0)
```

Arguments

object	a vector, numeric or equivalent (date, logical...)
level	the confidence level required
B	if >0, the number of bootstraps

Value

the vector [conf_inf, conf_sup]

Author(s)

Dan Chaltiel

Examples

```
confint_numeric(iris$Sepal.Length)
confint_numeric(mtcars2$hp_date)
confint_numeric(mtcars2$hp_date, level=0.99)
```

cross_summary	<i>Summarize a numeric vector</i>
---------------	-----------------------------------

Description

Summarize a numeric vector with min, max, mean, sd, median, IQR, n and missings.

Usage

```
cross_summary(x, dig = 1, ...)
```

Arguments

x	a numeric vector
dig	number of digits
...	params to pass on to format_fixed() : zero_digits and only_round

Value

a list of named functions

Author(s)

Dan Chaitiel, David Hajage

Examples

```
cross_summary(iris$Sepal.Length)
cross_summary(iris$Petal.Width, dig=3)
cross_summary(mtcars2$hp_date)
cross_summary(mtcars2$qsec_posix, date_format="%d/%m %H:%M")
```

crosstable

Easily describe datasets

Description

Generate a descriptive table of all chosen columns, as contingency tables for categorical variables and as calculation summaries for numeric variables. If the `by` argument points to one or several categorical variables, `crosstable` will output a description of all columns for each level. Otherwise, if it points to a numeric variable, `crosstable` will calculate correlation coefficients with all other selected numeric columns. Finally, if it points to a `Surv` object, `crosstable` will describe the survival at different times.

Can be formatted as an HTML table using [as_flextable\(\)](#).

Usage

```
crosstable(
  data,
  cols = everything(),
  ...,
  by = NULL,
  total = c("none", "row", "column", "both"),
  percent_pattern = "{n} ({p_row})",
  percent_digits = 2,
  num_digits = 1,
  showNA = c("ifany", "always", "no"),
  label = TRUE,
  funs = c(` ` = cross_summary),
  funs_arg = list(),
  cor_method = c("pearson", "kendall", "spearman"),
  drop_levels = FALSE,
  remove_zero_percent = NULL,
  unique_numeric = 3,
```

```

    date_format = NULL,
    times = NULL,
    followup = FALSE,
    test = FALSE,
    test_args = crosstable_test_args(),
    effect = FALSE,
    effect_args = crosstable_effect_args(),
    margin = deprecated(),
    .vars = deprecated()
  )

```

Arguments

data	A data.frame
cols	<tidy-select> Columns to describe, default to everything(). See examples or vignette("crosstable-selection") for more details.
...	Unused. All parameters after this one must be named.
by	The variable to group on. Character or name.
total	one of ["none", "row", "column" or "both"] to indicate whether to add total rows and/or columns. Default to none.
percent_pattern	Pattern used to describe proportions in categorical data. Syntax uses a glue::glue() specification, see the section below for more details. Default to "{n} ({p_col})" if by is null and "{n} ({p_row})" if it is not.
percent_digits	Number of digits for percentages.
num_digits	Number of digits for numeric summaries.
showNA	Whether to show NA in categorical variables (one of c("ifany", "always", "no"), like in table()).
label	Whether to show labels. See import_labels() or set_label() for how to add labels to the dataset columns.
funs	Functions to apply to numeric variables. Default to cross_summary() .
funs_arg	Additional parameters for funs, e.g. digits (the number of decimal places) for the default cross_summary() . Ultimately, these arguments are passed to format_fixed() .
cor_method	One of c("pearson", "kendall", "spearman") to indicate which correlation coefficient is to be used.
drop_levels	Whether to drop unused levels of factor variables. Default to TRUE.
remove_zero_percent	Whether to remove proportions when n==0. Default to FALSE.
unique_numeric	The number of non-missing different levels a variable should have to be considered as numeric.
date_format	A format string passed to format() for Date and POSIXt vectors. See strptime for formats. Can be set globally with crosstable_options(date_format = ...)

times	When using formula with <code>survival::Surv()</code> objects, which times to summarize.
followup	When using formula with <code>survival::Surv()</code> objects, whether to display follow-up time.
test	Whether to perform tests.
test_args	See <code>crosstable_test_args</code> to override default testing behaviour.
effect	Whether to compute a effect measure.
effect_args	See <code>crosstable_effect_args</code> to override default behaviour.
margin	Deprecated in favor of <code>percent_pattern</code> . One of ["row", "column", "cell", "none", or "all"]. Default to row.
.vars	Deprecated in favor of <code>cols</code> .

Value

A `data.frame/tibble` of class `crosstable`

About percent_pattern

The `percent_pattern` argument is very powerful but can be difficult to understand at first :

- It is usually a single string that uses the glue syntax, where variables are put in curly braces (`{x}`).
- Counts are expressed as `{n}`, `{n_row}`, `{n_col}`, and `{n_tot}`, and proportions as `{p_row}`, `{p_col}`, and `{p_cell}`, depending on the margin on which they are calculated.
- For each variable, a version including missing values in the total is proposed as `{n_xxx_na}` or `{p_xxx_na}`.
- For each proportion, a confidence interval is also calculated using **Wilson score** and can be expressed as `{p_xxx_inf}` and `{p_xxx_sup}`. See examples for practical applications.
- Alternatively, `percent_pattern` can be a list of characters with names `body`, `total_row`, `total_col`, and `total_all` to also control the pattern in other parts of the crosstable than the body.

Author(s)

Dan Chaltiel

See Also

<https://danchaltiel.github.io/crosstable/>, `as_flextable`, `import_labels`

Examples

```
#whole table
crosstable(iris)
crosstable(mtcars)
crosstable(mtcars2)
```

```

#tidyselection, custom functions
library(dplyr)
crosstable(mtcars2, c(ends_with("t"), starts_with("c")), by=vs,
           funs=c(mean, quantile), funs_arg=list(probs=c(.25,.75)))

#margin and totals, multiple by
crosstable(mtcars2, c(displacement, cyl), by=c(am, vs),
           margin=c("row", "col"), total = "both")

#predicate selection, correlation, effect calculation
crosstable(mtcars2, where(is.numeric), by=hp, effect=TRUE)

#lambda selection & statistical tests
crosstable(mtcars2, ~is.numeric(.x) && mean(.x)>50, by=vs, test=TRUE)

#Dates
mtcars2$my_date = as.Date(mtcars2$hp, origin="2010-01-01") %>% set_label("Some nonsense date")
crosstable(mtcars2, my_date, by=vs, date_format="%d/%m/%Y")

#Survival data (using formula syntax)
library(survival)
crosstable(aml, Surv(time, status) ~ x, times=c(0,15,30,150), followup=TRUE)

#Patterns
crosstable(mtcars2, vs, by=am, percent_digits=0,
           percent_pattern="{n} ({p_col} / {p_row})")
crosstable(mtcars2, vs, by=am, percent_digits=0,
           percent_pattern="N={n} \np[95%CI] = {p_col} [{p_col_inf}; {p_col_sup}]"
           str_high="n>5"; str_lo="n<=5"
crosstable(mtcars2, vs, by=am, percent_digits=0,
           percent_pattern="col={p_col}, row={p_row} ({ifelse(n<5, str_lo, str_high)})")

```

crosstable_effect_args

Default arguments for calculating and displaying effects in `crosstable()`

Description

This helper function provides default parameters for defining how the effect sizes should be computed. It belongs to the `effect_args` argument of the `crosstable()` function. See [effect_summary](#), [effect_tabular](#), and [effect_survival](#) for more insight.

Usage

```

crosstable_effect_args(
  effect_summarize = diff_mean_auto,
  effect_tabular = effect_odds_ratio,
  effect_survival = effect_survival_coxph,

```

```

effect_display = display_effect,
conf_level = 0.95,
digits = 2
)

```

Arguments

effect_summarize a function of three arguments (continuous variable, grouping variable and `conf_level`), used to compare continuous variable. Returns a list of five components: `effect` (the effect value(s)), `ci` (the matrix of confidence interval(s)), `effect.name` (the interpretation(s) of the effect value(s)), `effect.type` (the description of the measure used) and `conf_level` (the confidence interval level). Users can use [diff_mean_auto\(\)](#), [diff_mean_student\(\)](#), [diff_mean_boot\(\)](#), or [diff_median\(\)](#), or their custom own function.

effect_tabular a function of three arguments (two categorical variables and `conf_level`) used to measure the associations between two factors. Returns a list of five components: `effect` (the effect value(s)), `ci` (the matrix of confidence interval(s)), `effect.name` (the interpretation(s) of the effect value(s)), `effect.type` (the description of the measure used) and `conf_level` (the confidence interval level). Users can use [effect_odds_ratio\(\)](#), [effect_relative_risk\(\)](#), or [effect_risk_difference\(\)](#), or their custom own function.

effect_survival a function of two argument (a formula and `conf_level`), used to measure the association between a censored and a factor. Returns the same components as created by `effect_summarize`. Users can use [effect_survival_coxph\(\)](#) or their custom own function.

effect_display a function to format the effect. See [display_effect\(\)](#).

conf_level the desired confidence interval level

digits the decimal places

Value

A list with effect parameters

Author(s)

Dan Chaltiel

crosstable_options	<i>Options for the package crosstable</i>
--------------------	---

Description

Use this function to manage your crosstable parameters globally while taking advantage of auto-completion. Use [crosstable_peek_options\(\)](#) to see which option is currently set and [crosstable_reset_options\(\)](#) to set all options back to default.

Usage

```
crosstable_options(  
  ...,  
  remove_zero_percent = FALSE,  
  verbosity_autotesting = "default",  
  verbosity_duplicate_cols = "default",  
  total,  
  percent_pattern,  
  margin,  
  percent_digits,  
  num_digits,  
  showNA,  
  label,  
  funs,  
  funs_arg,  
  cor_method,  
  drop_levels,  
  unique_numeric,  
  date_format,  
  times,  
  followup,  
  test_args,  
  effect_args,  
  wrap_id = 70,  
  compact_padding = 25,  
  header_show_n_pattern = "{.col} (N={.n})",  
  keep_id,  
  by_header,  
  autofit,  
  compact,  
  collapse,  
  remove_header_keys,  
  show_test_name,  
  padding_v,  
  header_show_n,  
  fontsize_body,  
  fontsize_subheaders,  
  fontsize_header,  
  generic_labels,  
  units = "in",  
  peek_docx = TRUE,  
  font_code = "Consolas",  
  add_max_cols = 25,  
  gg_width,  
  gg_height,  
  format_legend_name,  
  table_legend_par_before,  
  table_legend_prefix,
```

```

figure_legend_par_after,
figure_legend_prefix,
normal_squish,
normal_font_size,
title_squish,
allow_break,
section_title,
section_title_level,
section_sentence,
style_normal,
style_image,
style_legend,
style_heading,
style_list_ordered,
style_list_unordered,
clean_names_fun,
verbosity_na_cols,
fishertest_B = 1e+05,
format_epsilon,
format_scientific,
zero_digits = 1,
.local = FALSE,
reset = deprecated()
)

```

Arguments

...	unused
remove_zero_percent	set to TRUE so that proportions are not displayed if n==0
verbosity_autotesting	one of default, quiet, or verbose
verbosity_duplicate_cols	one of default, quiet, or verbose.
total	For setting crosstable() arguments globally.
percent_pattern	For setting crosstable() arguments globally.
margin	For setting crosstable() arguments globally.
percent_digits	For setting crosstable() arguments globally.
num_digits	For setting crosstable() arguments globally.
showNA	For setting crosstable() arguments globally.
label	For setting crosstable() arguments globally.
funcs	For setting crosstable() arguments globally.
funcs_arg	For setting crosstable() arguments globally.
cor_method	For setting crosstable() arguments globally.

drop_levels	For setting crosstable() arguments globally.
unique_numeric	For setting crosstable() arguments globally.
date_format	For setting crosstable() arguments globally.
times	For setting crosstable() arguments globally.
followup	For setting crosstable() arguments globally.
test_args	For setting crosstable() arguments globally.
effect_args	For setting crosstable() arguments globally.
wrap_id	if id contains no spaces, wrap it with this maximum number of characters.
compact_padding	in flextables, left-padding for non-headers rows when compact=TRUE.
header_show_n_pattern	glue pattern used when showing N in the header of flextables. <code>.col</code> is the name of the column and <code>.n</code> the size of the group. Default to <code>{.col}</code> (<code>N={.n}</code>).
keep_id	For setting as_flextable() arguments globally.
by_header	For setting as_flextable() arguments globally.
autofit	For setting as_flextable() arguments globally.
compact	For setting as_flextable() arguments globally.
collapse	For setting as_flextable() arguments globally.
remove_header_keys	For setting as_flextable() arguments globally.
show_test_name	For setting as_flextable() arguments globally.
padding_v	For setting as_flextable() arguments globally.
header_show_n	For setting as_flextable() arguments globally.
fontsize_body	For setting as_flextable() arguments globally.
fontsize_subheaders	For setting as_flextable() arguments globally. Subheaders are only considered when compact=TRUE.
fontsize_header	For setting as_flextable() arguments globally.
generic_labels	For setting as_flextable() arguments globally.
units	default units in body_add_gg2() and body_add_img2()
peek_docx	behavior of peek() , which will open a docx if TRUE (default) and an xlsx if FALSE
font_code	font family used to show code, most likely a monospaced typeface such as Consolas (default)
add_max_cols	max number of columns a crosstable can have to be added to a Word document
gg_width, gg_height	cf. body_add_gg2()
format_legend_name	how the legend name ("Table", "Figure") is formatted. Default to <code>officer::fp_text_lite(bold=TRUE)</code>

`table_legend_par_before` whether to add an empty paragraph before all table legends
`table_legend_prefix, figure_legend_prefix` a prefix before each legend, after the numbering
`figure_legend_par_after` whether to add an empty paragraph after all figure legends
`normal_squish` Should you squish text in normal paragraphs?
`normal_font_size` Font size in normal paragraph, cf. `body_add_normal()`
`title_squish` Should you squish text in headers paragraphs?
`allow_break` allow crosstable rows to break across pages
`section_title, section_title_level, section_sentence` cf. `body_add_table_section()`
`style_normal` For specifying styles used in your {officer} template.
`style_image` For specifying styles used in your {officer} template.
`style_legend` For specifying styles used in your {officer} template.
`style_heading` For specifying styles used by headings on different levels. Levels will be pasted in the end (e.g. use "title" if your level 2 heading style is "title2").
`style_list_ordered, style_list_unordered` For specifying styles used by lists in the rdocx template. Needed for `body_add_list()` to work.
`clean_names_fun` cf. `clean_names_with_labels()`
`verbosity_na_cols` verbosity of a warning
`fishertest_B` number of simulations to perform when `fisher.test()` is failing (FEXACT error 7).
`format_epsilon` cf. `format_fixed()`
`format_scientific` the maximum power a number can have before being formatted as scientific. Default to 4 so applies on numbers $<1e-4$ or $>1e4$.
`zero_digits` default argument for `format_fixed()`
`.local` if TRUE, the effect will only apply to the local frame (thanks to `rlang::local_options()`)
`reset` if TRUE, set all these options back to default

Value

Nothing, called for its side effects

See Also

`crosstable_peek_options()` and `crosstable_reset_options()`

`crosstable_peek_options`*See which crosstable option is currently set.*

Description

See which crosstable option is currently set.

Usage

```
crosstable_peek_options(keep_null = FALSE)
```

Arguments

`keep_null` set to TRUE to get a list

Value

A named list of crosstable options

`crosstable_reset_options`*Reset all crosstable options.*

Description

Reset all crosstable options.

Usage

```
crosstable_reset_options(quiet = FALSE)
```

Arguments

`quiet` set to TRUE to remove the message.

Value

Nothing, called for its side effects

crosstable_test_args *Default arguments for calculating and displaying tests in [crosstable\(\)](#)*

Description

This is the starting point for refining the testing algorithm used in crosstable. Users can provide their own functions for test.~.

Usage

```
crosstable_test_args(
  test_summarize = test_summarize_auto,
  test_tabular = test_tabular_auto,
  test_correlation = test_correlation_auto,
  test_survival = test_survival_logrank,
  test_display = display_test,
  plim = 4,
  show_method = TRUE
)
```

Arguments

test_summarize	a function of two arguments (continuous variable and grouping variable), used to compare continuous variable. Must return a list of two components: p.value and method. See test_summarize_auto or test_summarize_linear_contrasts for some examples of such functions.
test_tabular	a function of two arguments (two categorical variables), used to test association between two categorical variables. Must return a list of two components: p.value and method. See test_tabular_auto for example.
test_correlation	a function of three arguments (two continuous variables plus the correlation method), used to test association between two continuous variables. Like cor.test, it must return a list of at least estimate, p.value, and method, with also conf.int optionally. See test_correlation_auto for example.
test_survival	a function of one argument (the formula surv~by), used to compare survival estimations. Must return a list of two components: p.value and method. See test_survival_logrank for example.
test_display	function used to display the test result. See display_test .
plim	number of digits for the p value.
show_method	whether to display the test name (logical).

Value

A list with test parameters

Author(s)

Dan Chaitiel

See Also

[test_summarize_auto](#), [test_tabular_auto](#), [test_survival_logrank](#), [test_summarize_linear_contrasts](#), [display_test](#)

Examples

```
library(dplyr)
my_test_args=crosstable_test_args()
my_test_args$test_summarize = test_summarize_linear_contrasts
iris %>%
  mutate(Petal.Width.qt = paste0("Q", ntile(Petal.Width, 5)) %>% ordered()) %>%
  crosstable(Petal.Length ~ Petal.Width.qt, test=TRUE, test_args = my_test_args)
```

ct_bind_cols

*Combine crosstables***Description****[Experimental]**

Combine multiple crosstables into one. This makes it possible to have multi-column crosstables with intra-group margins. A better solution will be found later.

Usage

```
ct_bind_cols(...)
```

Arguments

... crosstable objects

Value

a wider crosstable

Examples

```
ct1 = mtcars2 %>%
  crosstable(c(displ, cyl), by=c(am, vs),
    margin=c("row", "col"))

ct2 = mtcars2 %>%
  dplyr::mutate(vs="Total") %>%
  crosstable(c(displ, cyl), by=c(am, vs),
    margin=c("row", "col"))
```

```
ct_bind_cols(ct1, ct2) %>%
  af(header_show_n=TRUE)
```

ct_compact

Generic function to compact a table (publication formatting)

Description

Generic function to compact a table (publication formatting)

Usage

```
## S3 method for class 'data.frame'
ct_compact(
  data,
  name_from,
  name_to = "variable",
  ...,
  id_from = name_from,
  keep_id = TRUE,
  collapse = NULL,
  wrap_cols = NULL,
  rtn_flextable = FALSE
)

## S3 method for class 'crosstable'
ct_compact(
  data,
  name_from = "label",
  name_to = "variable",
  id_from = ".id",
  label_with_id = FALSE,
  keep_id = TRUE,
  ...
)
```

Arguments

data	the object to compact
...	additional arguments (not used)
name_from	name of the column to be collapsed when compacting
name_to	name of the column that will receive the collapsed column. Will be created if it doesn't exist.
id_from	name of the columns to use as cut-off. Useful when successive name_from have the same value.
keep_id	whether to keep id_from in the output.

collapse	levels to collapse into one row.
wrap_cols	name of the columns to wrap
rtn_flextable	whether to return a formatted <code>flextable::flextable()</code> object or a simple <code>data.frame</code>
label_with_id	glue pattern to keep the column name along with the label. If TRUE, default to "{label} ({.id})".

Value

a compacted data.frame

Author(s)

Dan Chaltiel

Examples

```
#dataframes
x=iris[c(1:5,51:55,101:105),]
ct_compact(x, name_from="Species")
ct_compact(x, name_from="Species", name_to="Petal.Length")
x$Species2 = substr(x$Species, 1, 1)
ct_compact(x, name_from="Species", wrap_cols="Species2")
ct_compact(x, name_from="Species", id_from="Species2") #cut on "v"

#crosstables
x=crosstable(mtcars2, c(displ, hp, am), by=vs, test=TRUE, effect=TRUE)
ct_compact(x)
ct_compact(x, name_from=".id")
```

display_effect	<i>Default function to display the effect</i>
----------------	---

Description

User can provide their own custom version in `crosstable_effect_args()`

Usage

```
display_effect(effect, digits = 4)
```

Arguments

effect	effect
digits	digits

Value

a character vector

Author(s)

Dan Chaltiel

display_test	<i>Default function to display a test result</i>
--------------	--

Description

Default function to display a test result

Usage

```
display_test(test, digits = 4, method = TRUE)
```

Arguments

test	test
digits	number of digits
method	display method

Value

a string

Author(s)

Dan Chaltiel

docx_bookmarks2	<i>List Word bookmarks, including the ones in header and footer</i>
-----------------	---

Description

This is a correction of `officer::docx_bookmarks()`. See [this PR](#).

Usage

```
docx_bookmarks2(
  x,
  return_vector = FALSE,
  target = c("all", "header", "body", "footer")
)
```

Arguments

x an rdocx object
return_vector use TRUE for compatibility with `officer::docx_bookmarks()`
target one of c("all", "header", "body", "footer")

Value

a list with all bookmarks

Author(s)

Dan Chaltiel

effect_summary	<i>Effect measure for association between one continuous and one categorical variable</i>
----------------	---

Description

User can either use or extend these functions to configure effect calculation.

Usage

```
diff_mean_auto(x, by, conf_level = 0.95, R = 500)  
diff_mean_boot(x, by, conf_level = 0.95, R = 500)  
diff_median_boot(x, by, conf_level = 0.95, R = 500)  
diff_mean_student(x, by, conf_level = 0.95)
```

Arguments

x numeric vector
by categorical vector (of exactly 2 unique levels)
conf_level confidence interval level
R number of bootstrap replication

Value

A list with five components: effect, ci, effect.name, effect.type, and conf_level

Functions

- `diff_mean_auto()`: (**Default**) calculate a specific "difference in means" effect based on normality (Shapiro or Anderson test) and variance homogeneity (Bartlett test)
- `diff_mean_boot()`: calculate a "difference in means" effect with a bootstrapped CI using standard deviation
- `diff_median_boot()`: calculate a "difference in medians" effect with a bootstrapped CI using quantiles#
- `diff_mean_student()`: calculate a "difference in means" effect using `t.test` confidence intervals

Author(s)

Dan Chaltiel, David Hajage

See Also

[crosstable_effect_args\(\)](#)

effect_survival	<i>Effect measure for association between one censored variable and one categorical variable</i>
-----------------	--

Description

Effect measure for association between one censored variable and one categorical variable

Usage

```
effect_survival_coxph(x, by, conf_level = 0.95)
```

Arguments

<code>x</code>	survival vector (made using survival::Surv())
<code>by</code>	categorical vector (of exactly 2 unique levels)
<code>conf_level</code>	confidence interval level

Value

a list with two components: `p.value` and `method`

Author(s)

Dan Chaltiel, David Hajage

effect_tabular*Effect measure for association between two categorical variables*

Description

User can either use or extend these functions to configure effect calculation.

Usage

```
effect_odds_ratio(x, by, conf_level = 0.95)
```

```
effect_relative_risk(x, by, conf_level = 0.95)
```

```
effect_risk_difference(x, by, conf_level = 0.95)
```

Arguments

x	categorical vector (character, factor, ...)
by	categorical vector (of exactly 2 unique levels)
conf_level	confidence interval level

Value

A list with five components: effect, ci, effect.name, effect.type, and conf_level

Functions

- `effect_odds_ratio()`: **(Default)** calculate the odds ratio
- `effect_relative_risk()`: calculate the relative risk
- `effect_risk_difference()`: calculate the risk difference

Author(s)

Dan Chaltiel, David Hajage

See Also

[crosstable_effect_args\(\)](#)

format_fixed	<i>Format values for display</i>
--------------	----------------------------------

Description

Format numeric values for display in tables and inline text. `format_fixed()` supports fixed or scientific notation, percentages, dates, and small-value formatting through `epsilon` and `zero_digits`.

Usage

```
format_fixed(  
  x,  
  digits = 1,  
  ...,  
  scientific = 4,  
  zero_digits = 1,  
  percent = FALSE,  
  date_format = NULL,  
  epsilon = NULL,  
  is_period = FALSE,  
  only_round = "deprecated"  
)
```

Arguments

x	A numeric vector to format. Can also be a Date, POSIXt, or Period.
digits	number of decimals places in decimal notation or number of significant digits in scientific notation.
...	Not used.
scientific	Order of magnitude beyond which numbers are printed in scientific notation. For example, <code>scientific = 4</code> prints values of order $10^{\pm 4}$ or larger in scientific notation. Can also be TRUE (always) or FALSE (never). Can be set globally with <code>crosstable_options(format_scientific = ...)</code> .
zero_digits	Number of significant digits to use for non-zero values that would otherwise round to 0. Use NULL to disable this behavior. Can be set globally with <code>crosstable_options(zero_digits = ...)</code> .
percent	If TRUE, values are formatted as percentages.
date_format	A format string passed to <code>format()</code> for Date and POSIXt vectors. See strptime for formats. Can be set globally with <code>crosstable_options(date_format = ...)</code>
epsilon	Values smaller than <code>epsilon</code> are displayed as " <code>< [epsilon]</code> ". Can be set globally with <code>crosstable_options(format_epsilon = ...)</code> .
is_period	Whether x is a period (a numeric value of seconds). Mainly for internal use.
only_round	Deprecated, use <code>zero_digits=NULL</code> instead.

Value

A character vector of formatted numbers

Author(s)

Dan Chaltiel

Examples

```
# Basic formatting
x = c(1, 1.2, 99.999, pi, 0.00000012)
format_fixed(x, digits = 2)

# Prevent small values from rounding to zero
x = c(1.1, 0.1, 0.008280661)
format_fixed(x, digits = 1, zero_digits = 1)

# Control when scientific notation is used
x = c(0.11e-04, 0.001, 0.01, 0.1, 1, 10)
format_fixed(x, scientific = 2, digits = 2)

# Force scientific or fixed notation
x = c(0.5, 0.01, 1e-07)
format_fixed(x, scientific = TRUE, digits = 1)
format_fixed(x, scientific = FALSE, digits = 4)

# Percent formatting
x = c(0.5, 0.1001, 0.01)
format_fixed(x, percent = TRUE, digits = 1)

# Threshold display for very small values
x = c(0.5, 0.1, 0.01)
format_fixed(x, epsilon = 0.05)
```

generate_autofit_macro

Generate a macro file for autofitting

Description

Autofitting using existing tools in flextable should be enough for most cases. For the others, here is a VBA macro which autofits all tables from inside MS Word. This function generates a file that can be imported into MS Word in order to use this macro. The macro file should be imported only once per computer.

Usage

generate_autofit_macro()

Value

Nothing, called for its side effects

Installation

- In the R console, run `generate_autofit_macro()` to generate the file `crosstable_autofit.bas` in your working directory.
- In MS Word, press `Alt+F11` to open the VB Editor.
- In the Editor, go to `File > Import` or press `Ctrl+M` to open the import dialog, and import `crosstable_autofit.bas`. There should now be a "CrosstableMacros" module in the "Normal" project.
- Run the macro, either from the VB Editor or from `View > Macros > View Macros > Run`.

This process will make the macro accessible from any Word file on this computer. Note that, in the Editor, you can also drag the module to your document project to make the macro accessible only from this file. The file will have to be named with the `docm` extension though.

Author(s)

Dan Chaltiel

get_label

Get variable labels, or return a default value

Description

Returns the "label" attribute of `x` when available. If no label is found, `default` is returned instead.

Usage

```
get_label(
  x,
  default = names(x),
  object = FALSE,
  recursive = FALSE,
  simplify = TRUE
)
```

Arguments

<code>x</code>	A labelled object. If <code>x</code> is a list or data frame, labels can be retrieved recursively from its elements.
<code>default</code>	Value returned when no label is found. Defaults to <code>names(x)</code> .
<code>object</code>	Logical. If <code>TRUE</code> , and <code>x</code> is a list or data frame, return the label of <code>x</code> itself instead of the labels of its children.

recursive	Logical. If TRUE, recurse into nested lists. Otherwise, labels are only retrieved from the first level.
simplify	Logical. If TRUE and object = FALSE, simplify the result to a character vector when possible. Otherwise, return a list.

Details

If `x` is a list or a data frame, `get_label()` returns the labels of its elements by default. Use `object = TRUE` to retrieve the label of the object itself instead.

Value

A character vector when `simplify = TRUE`, or a list otherwise.

Author(s)

Dan Chaltiel

See Also

[set_label\(\)](#), [import_labels\(\)](#), [remove_label\(\)](#), [Hmisc::label\(\)](#), [expss::var_lab\(\)](#)

Examples

```
xx=mtcars2 %>%
  set_label("The mtcars2 dataset", object=TRUE)
xx$cyl=remove_label(xx$cyl)

#vectors
get_label(xx$mpg) #label="Miles/(US) gallon"
get_label(xx$cyl) #default to NULL (since names(xx$cyl)==NULL)
get_label(xx$cyl, default="Default value")

#data.frames
get_label(xx)
get_label(xx, object=TRUE)
data.frame(name=names(xx), label=get_label(xx, default=NA)) #cyl is NA

#lists
get_label(list(xx$cyl, xx$mpg))          #cyl is NA
get_label(list(foo=xx$cyl, bar=xx$mpg))  #default to names
get_label(list(foo=xx$cyl, bar=xx$mpg), default="Default value")
```

get_percent_pattern	<i>Percent pattern helper</i>
---------------------	-------------------------------

Description

Get a list with pre-filled values for percent_pattern.

Usage

```
get_percent_pattern(  
  margin = c("row", "column", "cell", "none", "all"),  
  na = FALSE,  
  warn_duplicates = TRUE  
)
```

Arguments

margin	a vector giving the margins to compute.
na	whether to use NA
warn_duplicates	whether to warn if margin has duplicates

Value

a list

Examples

```
get_percent_pattern(c("cells", "row", "column"))  
get_percent_pattern(c("cells", "row", "column"), na=TRUE)
```

import_labels	<i>Import labels</i>
---------------	----------------------

Description

import_labels imports labels from a data.frame (data_label) to another one (.tbl). Works in synergy with [save_labels\(\)](#).

save_labels saves the labels from a data.frame in a temporary variable that can be retrieve by import_labels.

Usage

```
import_labels(
  .tbl,
  data_label,
  name_from = "name",
  label_from = "label",
  warn_name = FALSE,
  warn_label = FALSE,
  verbose = deprecated()
)

save_labels(.tbl)
```

Arguments

<code>.tbl</code>	the data.frame to be labelled
<code>data_label</code>	a data.frame from which to import labels. If missing, the function will take the labels from the last dataframe on which <code>save_labels()</code> was called.
<code>name_from</code>	in <code>data_label</code> , which column to get the variable name (default to <code>name</code>)
<code>label_from</code>	in <code>data_label</code> , which column to get the variable label (default to <code>label</code>)
<code>warn_name</code>	if TRUE, displays a warning if a variable name is not found in <code>data_label</code>
<code>warn_label</code>	if TRUE, displays a warning if a label is not found in <code>.tbl</code>
<code>verbose</code>	deprecated

Value

A dataframe, as `.tbl`, with labels

`.tbl` invisibly. Used only for its side effects.

Author(s)

Dan Chaitiel

See Also

`get_label()`, `set_label()`, `remove_label()`, `save_labels()`

Examples

```
#import the labels from a data.frame to another
iris_label = data.frame(
  name=c("Sepal.Length", "Sepal.Width",
        "Petal.Length", "Petal.Width", "Species"),
  label=c("Length of Sepals", "Width of Sepals",
         "Length of Petals", "Width of Petals", "Specie name")
)
iris %>%
  import_labels(iris_label) %>%
```

```

  crosstable

#save the labels, use some dplyr label-removing function, then retrieve the labels
library(dplyr)
mtcars2 %>%
  save_labels() %>%
  transmute(displacement=as.numeric(displacement)+1) %>%
  import_labels(warn_label=FALSE) %>% #
  crosstable(displacement)

```

iris2

Modified iris dataset

Description

Modified iris dataset so:

- every column is labelled (using label attribute)
- Species column is considered as factor

See [iris](#) for more informations on the original "Edgar Anderson's Iris Data" dataset.

Usage

```
iris2
```

Format

A data frame with 150 observations on 5 variables with labels.

Source

```

library(dplyr)
iris2 = iris %>%
  expss::apply_labels( #I also could have used [import_labels] or even `labelled::set_variable_labels`
    Species = "Species",
    Sepal.Length = "Length of Sepal",
    Sepal.Width = "Width of Sepal",
    Petal.Length = "Length of Petal",
    Petal.Width = "Width of Petal"
  ) %>%
  as_tibble()

```

Examples

```

library(crosstable)
ct=crosstable(iris2, by=Species)
ct
as_flextable(ct)

```

is.crosstable	<i>Test if an object is a crosstable</i>
---------------	--

Description

Test if an object is a crosstable

Usage

```
is.crosstable(x)
```

```
is.transposed_crosstable(x)
```

```
is.compacted_crosstable(x)
```

```
is.multiby_crosstable(x)
```

Arguments

x	An object
---	-----------

Value

TRUE if the object inherits from the crosstable class or other subclasses.

mtcars2	<i>Modified mtcars dataset</i>
---------	--------------------------------

Description

Modified mtcars dataset so:

- every column is labelled (using label attribute)
- rownames are a character column named model
- gear and cyl columns are considered as numerical factors
- vs and am columns are considered as character vector

See [mtcars](#) for more informations on the original "Motor Trend Car Road Tests" dataset.

Usage

```
mtcars2
```

Format

A data frame with 32 observations on 11 variables with labels.

Source

```
library(dplyr)
mtcars2 = mtcars %>%
  mutate(
    model=rownames(mtcars),
    vs=ifelse(vs==0, "vshaped", "straight"),
    am=ifelse(am==0, "auto", "manual"),
    across(c("cyl", "gear"), factor),
    .before=1
  ) %>%
  expss::apply_labels( #I also could have used [import_labels] or even `labelled::set_variable_labels`
    mpg="Miles/(US) gallon",
    cyl="Number of cylinders",
    disp="Displacement (cu.in.)",
    hp="Gross horsepower",
    drat="Rear axle ratio",
    wt="Weight (1000 lbs)",
    qsec="1/4 mile time",
    vs="Engine",
    am="Transmission",
    gear="Number of forward gears",
    carb="Number of carburetors"
  )
```

Examples

```
library(crosstable)
ct=crosstable(mtcars2, by=vs)
ct
as_flextable(ct)
```

N	<i>Return the number of non NA observations</i>
---	---

Description

Return the number of non NA observations

Usage

```
N(x)
```

Arguments

x a vector

Value

integer, number of non NA observations

Author(s)

David Hajage

na	<i>Return the number of NA observations</i>
----	---

Description

Return the number of NA observations

Usage

na(x)

Arguments

x a vector

Value

integer, number of NA observations

Author(s)

David Hajage

narm	<i>Remove missing values</i>
------	------------------------------

Description

Remove missing values

Usage

narm(x)

Arguments

x a vector

Value

the same vector without missing values

peek	<i>Open a crosstable in a temporary document</i>
------	--

Description

This eases copy-pasting

Usage

```
peek(x, docx = getOption("crosstable_peek_docx", TRUE), ...)
```

Arguments

x	a crosstable
docx	if true, peek as a docx, else, peek as xlsx
...	passed on to <code>as_flextable.crosstable()</code> or to <code>as_workbook()</code>

Value

Nothing, called for its side effects

Author(s)

Dan Chaltiel

pivot_crosstable	<i>Pivot a crosstable</i>
------------------	---------------------------

Description

Pivot a crosstable so the variable column is spread across its values.

Usage

```
pivot_crosstable(ct)
```

Arguments

ct	a crosstable
----	--------------

Value

a tibble of class `pivoted_crosstable`

Examples

```
ct = crosstable(mtcars2, c(mpg, drat, wt, qsec))
p_ct = pivot_crosstable(ct)
as_flextable(p_ct)
```

plim	<i>Format p values (alternative to format.pval())</i>
------	---

Description

Format p values (alternative to [format.pval\(\)](#))

Usage

```
plim(p, digits = 4)
```

Arguments

p	p values
digits	number of digits

Value

formatted p values

Author(s)

David Hajage

See Also

[format.pval\(\)](#), <https://stackoverflow.com/a/23018806/3888000>

remove_labels	<i>Remove all label attributes.</i>
---------------	-------------------------------------

Description

Use `remove_labels()` to remove the label from an object or to recursively remove all the labels from a collection of objects (such as a list or a `data.frame`).

This can be useful with functions reacting badly to labelled objects.

Usage

```
remove_labels(x)
```

Arguments

x object to unlabel

Value

An object of the same type as x, with no labels

Author(s)

Dan Chaltiel

See Also

[get_label](#), [set_label](#), [import_labels](#), [expss::unlab](#)

Examples

```
mtcars2 %>% remove_labels %>% crosstable(mpg) #no label
mtcars2$hp %>% remove_labels %>% get_label() #NULL
```

rename_with_labels	<i>Rename every column of a dataframe with its label</i>
--------------------	--

Description

Rename every column of a dataframe with its label

Usage

```
rename_with_labels(df, cols = everything(), except = NULL)
```

Arguments

df a data.frame

cols [<tidy-select>](#) columns to be renamed.

except [<tidy-select>](#) columns not be renamed. Deprecated in favor of cols.

Value

A dataframe which names are copied from the label attribute

Examples

```
rename_with_labels(mtcars2[,1:5], cols=1:4) %>% names()
rename_with_labels(iris2, cols=-c(Sepal.Length, Sepal.Width)) %>% names()
```

set_label	<i>Set the "label" attribute of an object</i>
-----------	---

Description

Set the "label" attribute of an object

Copy the label from one variable to another

Usage

```
set_label(x, value, object = FALSE)
```

```
copy_label_from(x, from)
```

Arguments

x	the variable to label
value	value of the label. If x is a list/data.frame, the labels will all be set recursively. If value is a function, it will be applied to the current labels of x.
object	if x is a list/data.frame, object=TRUE will force setting the labels of the object instead of the children
from	the variable whose label must be copied

Value

An object of the same type as x, with labels

Author(s)

Dan Chaltiel

See Also

[get_label\(\)](#), [import_labels\(\)](#), [remove_label\(\)](#)

Examples

```
library(dplyr)
mtcars %>%
  mutate(mpg2=set_label(mpg, "Miles per gallon"),
         mpg3=mpg %>% copy_label_from(mpg2)) %>%
  crosstable(c(mpg, mpg2, mpg3))
mtcars %>%
  copy_label_from(mtcars2) %>%
  crosstable(c(mpg, vs))
mtcars2 %>% set_label(toupper) %>% get_label()
```

summaryFunctions	<i>Summary functions</i>
------------------	--------------------------

Description

Summary functions to use with `crosstable()` or anywhere else.

Usage

```
meansd(x, na.rm = TRUE, dig = 2, ...)
meanCI(x, na.rm = TRUE, dig = 2, level = 0.95, format = TRUE, ...)
mediqr(x, na.rm = TRUE, dig = 2, format = TRUE, ...)
minmax(x, na.rm = TRUE, dig = 2, ...)
nna(x)
```

Arguments

<code>x</code>	a numeric vector
<code>na.rm</code>	TRUE as default
<code>dig</code>	number of digits
<code>...</code>	params to pass on to <code>format_fixed()</code> : <ul style="list-style-type: none"> • <code>zero_digits</code> (default=1): the number of significant digits for values rounded to 0 (set to NULL to keep the original 0 value) • <code>only_round</code> (default=FALSE): use <code>round()</code> instead of <code>format_fixed()</code>
<code>level</code>	the confidence level required
<code>format</code>	a sugar argument. If FALSE, the function returns a list instead of a formatted string

Value

a character vector

Functions

- `meansd()`: returns mean and std error
- `meanCI()`: returns mean and confidence interval
- `mediqr()`: returns median and IQR
- `minmax()`: returns minimum and maximum
- `nna()`: returns number of observations and number of missing values

Fixed format

These functions use `format_fixed()` which allows to have trailing zeros after rounded values. In the case when the output of rounded values is zero, the use of the `zero_digits` argument allows to keep some significant digits for this specific case only.

Author(s)

Dan Chaltiel, David Hajage

See Also

`format_fixed()`

Examples

```
meansd(iris$Sepal.Length, dig=3)
meanCI(iris$Sepal.Length)
minmax(iris$Sepal.Length, dig=3)
mediqr(iris$Sepal.Length, dig=3)
nna(iris$Sepal.Length)

#arguments for format_fixed
x = iris$Sepal.Length/10000 #closer to zero

meansd(x, dig=3)
meansd(x, dig=3, zero_digits=NULL) #or NA
meansd(x, dig=3, only_round=TRUE)
options("crosstable_only_round"=TRUE)
meansd(x, dig=3, zero_digits=2)
options("crosstable_only_round"=NULL)
meanCI(mtcars2$hp_date)

#dates
x = as.POSIXct(mtcars$qsec*3600*24 , origin="2010-01-01")
meansd(x)
minmax(x, date_format="%d/%m/%Y")
```

`test_correlation_auto` *test for correlation coefficients*

Description

test for correlation coefficients

Usage

```
test_correlation_auto(x, by, method)
```

Arguments

x	vector
by	another vector
method	"pearson", "kendall", or "spearman"

Value

the correlation test with appropriate method

Author(s)

Dan Chaltiel, David Hajage

test_summarize_auto	<i>test for mean comparison</i>
---------------------	---------------------------------

Description

Compute a oneway.test (with equal or unequal variance) or a kruskal.test as appropriate.

Usage

```
test_summarize_auto(x, g)
```

Arguments

x	vector
g	another vector

Value

a list with two components: p.value and method

Author(s)

Dan Chaltiel, David Hajage

`test_summarize_linear_contrasts`*Test for linear trend across ordered factor with contrasts*

Description

Test for linear trend across ordered factor with contrasts

Usage

```
test_summarize_linear_contrasts(x, y)
```

Arguments

x	vector
y	ordered factor

Value

a list with two components: p.value and method

Author(s)

Dan Chaltiel

Examples

```
library(dplyr)
my_test_args=crosstable_test_args()
my_test_args$test_summarize = test_summarize_linear_contrasts
iris %>%
  mutate(Petal.Width.qt = paste0("Q", ntile(Petal.Width, 5)) %>% ordered()) %>%
  crosstable(Petal.Length ~ Petal.Width.qt, test=TRUE, test_args = my_test_args)
```

`test_survival_logrank` *test for survival comparison*

Description

Compute a logrank test

Usage

```
test_survival_logrank(formula)
```

Arguments

formula a formula

Value

a list with two components: p.value and method

Author(s)

Dan Chaltiel, David Hajage

test_tabular_auto	<i>test for contingency table</i>
-------------------	-----------------------------------

Description

Compute a `chisq.test`, a `chisq.test` with correction of continuity or a fisher test as appropriate

Usage

```
test_tabular_auto(x, y)
```

Arguments

x vector
y another vector

Value

a list with two components: p.value and method

Author(s)

Dan Chaltiel, David Hajage

transpose_crosstable	<i>Transpose a crosstable</i>
----------------------	-------------------------------

Description

Pivot a crosstable so the label column is swapped with the by row. This requires the variable column to be the same for every data column, like when all columns are numeric or when all columns are factors with the same levels

Usage

```
transpose_crosstable(x)

## S3 method for class 'crosstable'
t(x)
```

Arguments

x a crosstable

Value

a tibble of class transposed_crosstable

Examples

```
ct = crosstable(mtcars2, c(mpg, drat, wt, qsec), by=am)
ct %>% t() %>% as_flextable()
ct2 = crosstable(mtcars2, c(mpg, drat, wt, qsec), by=c(am, vs))
ct2 %>% t() %>% as_flextable()
```

write_and_open	<i>Alternative to default officer print() function. Write the file and try to open it right away.</i>
----------------	---

Description

As it tests if the file is writable, this function also prevents officer:::print.rdocx() to abort the RStudio session.

Usage

```
write_and_open(doc, docx.file, add_date = FALSE)
```

Arguments

doc	the docx object
docx.file	the name of the target file. If missing or NULL, the doc will open in a temporary file.
add_date	whether to add the current date before docx.file extension.

Value

Nothing, called for its side effects

Author(s)

Dan Chaltiel

Examples

```
library(officer)
library(crosstable)
mytable = crosstable(mtcars2)
doc = read_docx() %>%
  body_add_crosstable(mytable)

write_and_open(doc)
## Not run:
write_and_open(doc, "example.docx")
write_and_open(doc, "example.docx", add_date=TRUE)
write_and_open(doc, "example.docx", add_date=Sys.Date()-1)

## End(Not run)
```

Index

- * **as_gt methods**
 - as_gt.crosstable, 6
- * **datasets**
 - iris2, 52
 - mtcars2, 53
- af (as_flextable.crosstable), 4
- apply_labels, 3
- as_flextable (as_flextable.crosstable), 4
- as_flextable(), 28, 35
- as_flextable.crosstable, 4
- as_flextable.crosstable(), 7, 9
- as_gt (as_gt.crosstable), 6
- as_gt.crosstable, 6
- as_gt.crosstable(), 5
- as_workbook, 8
- body_add_crosstable, 9
- body_add_crosstable(), 9, 10, 21, 23
- body_add_crosstable_footnote, 10
- body_add_crosstable_list
 - (body_add_table_list), 21
- body_add_figure_legend
 - (body_add_legend), 14
- body_add_figure_legend(), 16
- body_add_flextable2, 11
- body_add_flextable_list
 - (body_add_table_list), 21
- body_add_gg2, 12
- body_add_gg2(), 14, 35
- body_add_glued (body_add_normal), 19
- body_add_img2, 13
- body_add_img2(), 35
- body_add_legend, 14
- body_add_list, 17
- body_add_list(), 36
- body_add_list_item (body_add_list), 17
- body_add_normal, 19
- body_add_normal(), 14–16, 18, 20, 24, 36
- body_add_table_legend
 - (body_add_legend), 14
- body_add_table_legend(), 11, 16
- body_add_table_list, 21
- body_add_table_section, 22
- body_add_table_section(), 36
- body_add_title, 23
- body_replace_text_at_bkms, 25
- clean_names_with_labels, 26
- clean_names_with_labels(), 36
- confint_numeric, 27
- copy_label_from (set_label), 59
- cross_summary, 27
- cross_summary(), 29
- cross_to_flextable
 - (as_flextable.crosstable), 4
- crosstable, 28
- crosstable(), 5, 8, 31, 34, 35, 38, 60
- crosstable_effect_args, 30, 31
- crosstable_effect_args(), 41, 44, 45
- crosstable_options, 32
- crosstable_options(), 5, 19
- crosstable_peek_options, 37
- crosstable_peek_options(), 32, 36
- crosstable_reset_options, 37
- crosstable_reset_options(), 32, 36
- crosstable_test_args, 30, 38
- ct_bind_cols, 39
- ct_compact, 40
- ct_compact.crosstable(), 5
- ctf (as_flextable.crosstable), 4
- diff_mean_auto (effect_summary), 43
- diff_mean_auto(), 32
- diff_mean_boot (effect_summary), 43
- diff_mean_boot(), 32
- diff_mean_student (effect_summary), 43
- diff_mean_student(), 32
- diff_median (effect_summary), 43

- diff_median(), 32
- diff_median_boot (effect_summary), 43
- display_effect, 41
- display_effect(), 32
- display_test, 38, 39, 42
- docx_bookmarks2, 42
- effect_odds_ratio (effect_tabular), 45
- effect_odds_ratio(), 32
- effect_relative_risk (effect_tabular), 45
- effect_relative_risk(), 32
- effect_risk_difference (effect_tabular), 45
- effect_risk_difference(), 32
- effect_summary, 31, 43
- effect_survival, 31, 44
- effect_survival_coxph (effect_survival), 44
- effect_survival_coxph(), 32
- effect_tabular, 31, 45
- expss::apply_labels(), 3
- expss::unlab, 58
- expss::var_lab(), 49
- flextable::body_add_flextable(), 11, 21, 23
- flextable::flextable(), 5, 41
- format(), 29, 46
- format.pval(), 57
- format_fixed, 46
- format_fixed(), 27, 29, 36, 60, 61
- generate_autofit_macro, 47
- get_label, 48, 58
- get_label(), 51, 59
- get_percent_pattern, 50
- ggplot2::ggsave(), 12
- glue::glue(), 29
- gt::gt(), 7
- Hmisc::label(), 49
- import_labels, 50, 58
- import_labels(), 29, 49, 59
- iris, 52
- iris2, 52
- is.compacted_crosstable (is.crosstable), 53
- is.crosstable, 53
- is.multiby_crosstable (is.crosstable), 53
- is.transposed_crosstable (is.crosstable), 53
- meanCI (summaryFunctions), 60
- meansd (summaryFunctions), 60
- mediqr (summaryFunctions), 60
- minmax (summaryFunctions), 60
- moystd (summaryFunctions), 60
- mtcars, 53
- mtcars2, 53
- N, 54
- na, 55
- narm, 55
- nna (summaryFunctions), 60
- officer::body_add_gg(), 12
- officer::body_add_img(), 13
- officer::body_add_par(), 17
- officer::docx_bookmarks(), 42, 43
- officer::fp_text(), 15
- officer::fp_text_lite(), 15
- officer::read_docx(), 9, 21
- peek, 56
- peek(), 35
- pivot_crosstable, 56
- plim, 57
- remove_label (remove_labels), 57
- remove_label(), 49, 51, 59
- remove_labels, 57
- rename_dataframe_with_labels (rename_with_labels), 58
- rename_with_labels, 58
- round(), 60
- save_labels (import_labels), 50
- save_labels(), 50, 51
- set_label, 58, 59
- set_label(), 29, 49, 51
- stats::confint, 27
- strptime, 29, 46
- summaryFunctions, 60
- survival::Surv(), 30, 44
- t.crosstable (transpose_crosstable), 65

`test_args (crosstable_test_args)`, [38](#)
`test_correlation_auto`, [38](#), [61](#)
`test_summarize_auto`, [38](#), [39](#), [62](#)
`test_summarize_linear_contrasts`, [38](#), [39](#),
 [63](#)
`test_survival_logrank`, [38](#), [39](#), [63](#)
`test_tabular_auto`, [38](#), [39](#), [64](#)
`to_flextable (as_flextable.crosstable)`,
 [4](#)
`transpose_crosstable`, [65](#)
`write_and_open`, [65](#)